

## TECHNICAL DATA SHEET

### FLUORMICRO P100+ MPS PTFE

#### PERCENTAGE COMPOSITION BY WEIGHT (%)

100% PTFE POWDER

PROPERTY	TEST METHOD	UNIT OF MEASURE	SPECIFICATION
<b>Colour</b>	Internal	VISUAL	WHITE
<b>Contamination</b>	Internal	VISUAL	MAX 3 POINTS WITH DIAMETER <100 Micron ON A 1 M BAR
<b>Humidity</b>	ASTM D750	%	0,008-0,020
<b>Density (apparent)</b>	ASTM 4894	g/l	950-1150
<b>Average particle size</b>	Internal	MICRON	220+-50 Micron

RCQ FLUORMETALL SRL

Rev. 00 dd. 04/06/2021

All this data is considered accurate and reliable but doesn't imply any guarantee whatsoever or responsibility on our part. This inspection certificate doesn't exempt Customers from carrying out their own O.C. at check-in.

*Operational headquarters:* Via Dell'Artigianato, 4 - Via Europa Unita, 16 - 24069 Trescore Balneario (BG) - Italia

*Registered office:* Via Cremasca, 24 - 24052 Azzano San Paolo (BG) - Italy

Tel. +39 035 4258560 Fax +39 035 942794

e-mail: [info@fluormetall.it](mailto:info@fluormetall.it) Pec: [fluormetall@arubapec.it](mailto:fluormetall@arubapec.it) Internet: [www.fluormetall.it](http://www.fluormetall.it)