

TECHNICAL DATA SHEET

FLUORMICRO M100 MPS PTFE

PERCENTAGE COMPOSITION BY WEIGHT (%)

100% MODIFIED PTFE POWDER

PROPERTY	TEST METHOD	UNIT OF MEASURE	SPECIFICATION
Colour	Internal	VISUAL	TRANSPARENT
Contamination	Internal	VISUAL	MAX 3 POINTS WITH DIAMETER <100 Micron ON A 1 M BAR
Humidity	ASTM D750	%	0,008-0,020
Density (apparent)	ASTM 4894	g/l	900-1100
Average particle size	Internal	MICRON	350+-50 Micron

RCQ FLUORMETALL SRL

Rev. 00 dd. 04/06/2021

All this data is considered accurate and reliable but doesn't imply any guarantee whatsoever or responsibility on our part. This inspection certificate doesn't exempt Customers from carrying out their own O.C. at check-in.

Operational headquarters: Via Dell'Artigianato, 4 - Via Europa Unita, 16 - 24069 Trescore Balneario (BG) - Italia

Registered office: Via Cremasca, 24 - 24052 Azzano San Paolo (BG) - Italy

Tel. +39 035 4258560 Fax +39 035 942794

e-mail: info@fluormetall.it Pec: fluormetall@arubapec.it Internet: www.fluormetall.it